

# SP 95 Impact Ball For Building Acoustics



SP95 Impact Ball is used for sound insulation testing in light weight structures where a standard (tapping machine) impact sound source would create too much impact force. It has been designed in accordance to ISO 10140-5 standard. The use of SP 95 Impact Ball is very easy - it is

dropped vertically in a free fall from height of 100 cm to the surface of the floor. In practise SP95 can be used to assess soft impacts related to human disturbance, such as children jumping.

Used for sound insulation testing in light weight structures where a standard (tapping machine) impact sound source would create too much impact force.

Used for low frequency impact noise insulation tests in the octave bands from 31,5 Hz to 500 Hz.

Meets ISO 10140-5 standard

Mass 2,5 kg and convenient size allows easy transportation and carrying.

Comfortable carrying bag included

Easy to clean using water



## What's inside?

The kit consist of SP95 Impact Ball with a carrying bag (fabric material). Each SP95 Impact Ball has 36 months warranty.

## Technical Specifications

Standards	IEC 10140-5:2011
Material	Silicone rubber
Diameter	180 mm
Weight	2,5 kg

Impact force exposure level in each octave band of the heavy/soft impact source

Octave band center frequency Hz	Impact force exposure level $L_{FE}$ dB re 1 N
31,5	39,0 +/- 1,0
63	31,0 +/- 1,5
125	23,0 +/- 1,5
250	17,0 +/- 2,0
500	12,5 +/- 2,0

SVANTEK Sp. z o. o.

ul. Strzygłowska 81, 04-872 WARSAW, POLAND  
phone/fax (+48) 22 51 88 320, (+48) 22 51 88 312  
<http://www.svantek.com> e-mail: [office@svantek.com.pl](mailto:office@svantek.com.pl)

Our Company's policy is based upon continuous product development and innovation. Therefore, we reserve the right to change the specifications without any prior notice whatsoever.